

Close

Print

◀ [1] ▶

Record 1 of 1

Title: Experimental validation of micromechanical models for brittle aluminium alloy foam**Author(s):** Marsavina, L (Marsavina, Liviu); Kovacik, J (Kovacik, Jaroslav); Linul, E (Linul, Emanoil)**Source:** THEORETICAL AND APPLIED FRACTURE MECHANICS **Volume:** 83 **Pages:** 11-18 **DOI:** 10.1016/j.tafmec.2015.12.020 **Published:** JUN 2016**Times Cited in Web of Science Core Collection:** 5**Total Times Cited:** 5**Usage Count (Last 180 days):** 4**Usage Count (Since 2013):** 7**Cited Reference Count:** 43

Abstract: Micromechanical models used to predict mechanical and fracture properties of brittle metallic foams are validated experimentally for closed-cell aluminium foam (AlSi12Mg0.6) prepared by powder metallurgy route. Compression, tensile, tensile on notched specimens and fracture toughness tests were carried on, and the results are presented together with micromechanical models from literature. Moreover, the Digital Image Correlation technique was applied to identify the failure mechanisms of aluminium foams. Finally, the Theory of Critical Distances was employed to predict the fracture load of notched specimens. The novelty of the study is that the inherent stresses and critical distances were obtained by employing micromechanical analysis. (C) 2016 Elsevier Ltd. All rights reserved.

Accession Number: WOS:000374357500003**Language:** English**Document Type:** Article**Author Keywords:** Aluminium foam; Micromechanical models; Mechanical properties; Fracture properties; Theory of Critical Distances; Digital Image Correlation**KeyWords Plus:** CRITICAL DISTANCES; METALLIC FOAMS; OPEN-CELL; TENSILE-STRENGTH; STATIC STRENGTH; CRACK ONSET; FRACTURE; DEFORMATION; NOTCH; BEHAVIOR**Addresses:** [Marsavina, Liviu; Linul, Emanoil] Univ Politehn Timisoara, Fac Mech Engr, Blvd M Viteazu 1, Timisoara 300222, Romania.

[Kovacik, Jaroslav] Slovak Acad Sci, Inst Mat & Machine Mech, Racianska 75, Bratislava 83102 3, Slovakia.

Reprint Address: Marsavina, L (reprint author), Univ Politehn Timisoara, Fac Mech Engr, Blvd M Viteazu 1, Timisoara 300222, Romania.**E-mail Addresses:** liviu.marsavina@upt.ro; ummsjk@savba.sk; linul_emanoil@yahoo.com**Author Identifiers:**

Author	ResearcherID Number	ORCID Number
Kovacik, Jaroslav	K-2556-2013	0000-0002-6970-0406
LINUL, Emanoil		0000-0001-9090-8917

Publisher: ELSEVIER SCIENCE BV**Publisher Address:** PO BOX 211, 1000 AE AMSTERDAM, NETHERLANDS**Web of Science Categories:** Engineering, Mechanical; Mechanics**Research Areas:** Engineering; Mechanics**IDS Number:** DJ6XW**ISSN:** 0167-8442**eISSN:** 1872-7638**29-char Source Abbrev.:** THEOR APPL FRACT MEC**ISO Source Abbrev.:** Theor. Appl. Fract. Mech.**Source Item Page Count:** 8**Funding:**

Funding Agency	Grant Number
Romanian National Authority for Scientific Research, CNCS-UEFISCDI	PN-II-ID-PCE-2011-3-0456 172/2011
Slovak Research and Development Agency	APVV-0692-12
UPT	SK-RO-0014-12 653/2013
SAS	SK-RO-0014-12 653/2013
Center of Excellence for Modern Composites Applied in Aerospace and Surface Transport Infrastructure	245479 FP7-REGPOT-2009-1

This work was supported by the Grant of the Romanian National Authority for Scientific Research, CNCS-UEFISCDI, project PN-II-ID-PCE-2011-3-0456, contract number 172/2011, Slovak Research and Development Agency under contract APVV-0692-12, bilateral agreement between UPT and SAS, contract no. SK-RO-0014-12 and 653/2013. The DIC measurements were possible with the support from Center of Excellence for Modern Composites Applied in Aerospace and Surface Transport Infrastructure, FP7-REGPOT-2009-1, under Grant agreement No: 245479. The help of Dr. T. Voiconi on experimental tests is also acknowledged.

Close

Print

◀ [1] ▶