

Close

Web of Science  
Page 1 (Records 1 -- 1)

Print



## Record 1 of 1

**Title:** The mechanical properties of expanded perlite-aluminium syntactic foam at elevated temperatures**Author(s):** Taherishargh, M (Taherishargh, Mehdi); Linul, E (Linul, Emanoil); Broxtermann, S (Broxtermann, Steffen); Fiedler, T (Fiedler, Thomas)**Source:** JOURNAL OF ALLOYS AND COMPOUNDS **Volume:** 737 **Pages:** 590-596 **DOI:** 10.1016/j.jallcom.2017.12.083 **Published:** MAR 15 2018**Times Cited in Web of Science Core Collection:** 4**Total Times Cited:** 4**Usage Count (Last 180 days):** 5**Usage Count (Since 2013):** 19**Cited Reference Count:** 23

**Abstract:** Expanded perlite/A356 aluminium syntactic foams (P-MSF) were produced via a counter-gravity infiltration process. The quasi-static compressive properties of these foams were investigated at 25, 125, 250, 375, and 500 degrees C and compared with those of the matrix material, tested at the same conditions. Young's modulus, offset yield stress, plateau stress and energy absorption was evaluated for all samples. The improved ductility of the foams at higher temperatures results in more uniform deformation and smoother stress-strain curves. At the same time, the mechanical strength and the energy absorption of the foams and the matrix material decrease. The results indicate that the high temperature mechanical properties of the foams are controlled by two counter-acting mechanisms, i.e. the softening of the matrix material and the improved ductility of the foam. (C) 2017 Elsevier B.V. All rights reserved.

**Accession Number:** WOS:000419212900071**Language:** English**Document Type:** Article**Author Keywords:** Metallic syntactic foam; High temperature properties; Elastic stiffness; Material strength**KeyWords Plus:** COMPRESSIVE DEFORMATION-BEHAVIOR; MATRIX COMPOSITES; INDENTATION**Addresses:** [Taherishargh, Mehdi; Broxtermann, Steffen; Fiedler, Thomas] Univ Newcastle, Sch Engr, Callaghan, NSW 2287, Australia.

[Linul, Emanoil] Politehn Univ Timisoara, Dept Mech &amp; Strength Mat, 1 Mihai Viteazu Ave, Timisoara 300222, Romania.

**Reprint Address:** Fiedler, T (reprint author), Univ Newcastle, Sch Engr, Callaghan, NSW 2287, Australia.**E-mail Addresses:** Thomas.Fiedler@newcastle.edu.au**Author Identifiers:**

Author	ResearcherID Number	ORCID Number
Fiedler, Thomas		0000-0003-0256-8233

**Publisher:** ELSEVIER SCIENCE SA**Publisher Address:** PO BOX 564, 1001 LAUSANNE, SWITZERLAND**Web of Science Categories:** Chemistry, Physical; Materials Science, Multidisciplinary; Metallurgy & Metallurgical Engineering**Research Areas:** Chemistry; Materials Science; Metallurgy & Metallurgical Engineering**IDS Number:** FR6YH**ISSN:** 0925-8388**eISSN:** 1873-4669**29-char Source Abbrev.:** J ALLOY COMPD**ISO Source Abbrev.:** J. Alloy. Compd.**Source Item Page Count:** 7**Output Date:** 2019-01-04

Close

Web of Science  
Page 1 (Records 1 -- 1)

Print



Clarivate

Accelerating innovation

© 2019 Clarivate

[Copyright notice](#)[Terms of use](#)[Privacy statement](#)[Cookie policy](#)[Sign up for the Web of Science newsletter](#)[Follow us](#)